

STORAGE WELL REPAIRS & MAINTENANCE PROCESS



1. >> 2. >> 3. >> 4. >> 5. >> 6.

EQUIPMENT RECEIVED

The wellhead is shipped to UWS facility where it is disassembled, cleaned and inspected.

DISASSEMBLY & CUSTOMER REQUESTS IMPLEMENTED

The wellhead spools, adapters & DSA's are then sandblasted, Xylan coated or Hempel coated, as required by the customer.

FITTINGS REPLACED

All lockscrews, stainless steel fittings such as cavity plugs, internal check valves or lube fittings are replaced.

WELLHEAD TESTED & ELASTOMERS REPLACED

The wellhead is tested to customer specifications and charted with copies for either customer or 3rd party inspector. All elastomers are replaced in all sealing areas.

EQUIPMENT PAINTED

The wellhead is painted with Zinc Type paint to withstand weather conditions such as off-shore type weather.

EQUIPMENT SHIPPED

When the wellhead is completed and shipped, UWS provides stainless steel ring gaskets, teflon coated studs/nuts and flange protectors.

UWS provides 24/7 service availability to install and test your wellhead once it is on the well, and UWS servicemen have certifications already in place at many storage well locations.

WWW.UNIVERSALWELLHEAD.COM | (318) 779-1829 | INFO@UNIVERSALWELLHEAD.COM

CORPUS CHRISTI, TX
5729 Leopard St., Bldg. 9
Corpus Christi, TX 78408

HOUSTON, TX
6401 Cunningham Rd,
Houston, TX 77041

ODESSA, TX
1541 Windcrest
Odessa, TX 79763

SHREVEPORT, LA
1710 N. Hearne Ave.
Shreveport, LA 71107

NEWCOMERSTOWN, OH
126 New Pace Rd.
Newcomerstown, OH 43832